

### Digimax S800





# The new fashion colour for great pictures is black

#### \* 8.1-megapixel CCD

The 1/1.8" CCD uses a tru-colour filter to produce fine detail images.

#### 3x optical SHD zoom lens plus 5x digital

The high definition zoom lens delivers sharper, clearer images and has a 35 mm equivalent of 35~105 mm. The 15x zoom is great for distance sports like Commonwealth Games athletics or swimming, football and surfing.

#### 5 cm Macro plus Auto Macro

Automatically alters the focus from 5 cm to infinity making every image sharp and clear, from flowers in the garden to the kids on the beach.

#### **★ Large 2.4" Hi-Resolution Monitor**

The  $2.4^{\prime\prime}$  TFT LCD Hi-Res monitor lets you see what you are taking and gives a clear view of what you have taken.

#### User friendly Mode Dial

The mode dial offers easy access to the auto, program, manual and scene modes plus the family friendly night, portrait and child modes.

#### MPEG-4 movies at 30 fps with sound

Take movies in MJPEG-4 at 30 fps and show them on TV. You'll get more than an hour of movies on a 256 MB SD card and edit them 'in-camera'.

#### 20 MB internal memory plus SD card slot

Images can then be easily transferred from the internal memory to a Secure Digital (SD) memory card and will accept memory cards up to 1 GB.

#### PictBridge USB 2.0 direct printing

The S800 has PictBridge direct printing with compatible printers and fast download of full resolution images to PC or portable hard drive via USB 2.0.

#### **\*** Quick print button

Combined with Direct Print Order Format (DPOF) allows you to print two of three or one each of ten prints or any other combination.

#### AA alkaline or Ni-MH batteries

Uses universally available AA alkaline or cost saving Nickel Metal Hydride batteries which can be recharged in minutes.

#### **PRODUCT 371274**

#### **SAMSUNG DIGITAL CAMERAS - SETTING THE TREND**





## Digimax \$800





Digima	x S800 Speci	fications	Digimax	S800 Speci	fications (cont)
Image Sensor	Туре	1/1.8 CCD		Media	Internal memory: 20 MB (approx.) flash memory
	Effective Pixel	Approx. 8.1 Megapixel			SD card / MMC (up to 1 Gb guaranteed)
	Total Pixel	Approx. 8.3 Megapixel		File Format	Still image: JPEG (DCF), Exif 2.2,
Lens	Focal Length	SHD lens f=7.4~22.2 mm (35 equiv: 35~105 mm)			DPOF 1.1, PictBridge 1.0
	F No.	F2.8 ~ F7.1 (W) F5.1 ~ F13.1 (T)			Movie Clip: MJPEG-4 (AVI), Audio WAV (voice memo
	Digital Zoom	Still image made: 1x~10x		Image Size	<b>8M</b> :3264x2448, <b>7M</b> :3072x2304, <b>6M</b> :2816x2112,
		Play mode: 1x ~ 12.8x (image size dependant)			<b>5M</b> :2592x1944, <b>4M</b> :2272x1704, <b>3M</b> :2048x1536,
LCD Monitor		2.4" colour TFT LCD (112,000 pixels)	1		<b>2M</b> :1600x1200, <b>1M</b> :1024x768, <b>VGA</b> :640x480
Focusing	Туре	TTL autofocus	Storage	Capacity* (20 MB)	8M: Super fine 4, Fine 9, Normal 13
	Range	Normal: 80 cm ~ infinity, Auto macro: 4 cm ~ infinity			<b>7M</b> : Super fine 5, Fine 10, Normal 15
		Macro: 4 cm ~ 80 cm (W), 50 cm ~ 80 cm (T)			6M: Super fine 6, Fine 12, Normal 17
Shutter	Туре	Mechanical and Electronic shutter			5M: Super fine 7, Fine 14, Normal 21
	Speed	1 ~ 1/1,500 sec (Manual: 8 sec ~ 1/1,500 sec)			4M: Super fine 9, Fine 18, Normal 22
Exposure	Control	Program AE			3M: Super fine 11, Fine 22, Normal 32
		Metering: Multi, Spot.			<b>2M</b> : Super fine 19, Fine 34, Normal 41
	Compensation	±2EV (0.5 steps)			1M: Super fine 41, Fine 69, Normal 83
	ISO Equivalent	Auto, 50, 100, 200, 400			VGA: Super fine 83, Fine 89, Normal 104
		Auto, Auto & Red-eye reduction			These figures depend on shooting conditions and are approximate on
	Modes	Fill-in, Slow sync, Flash off		Туре	Single image, Thumbnails, Slide show, Movie clip,
	Range	Wide: 0.2 ~ 3 m, Tele: 0.4 ~ 2.5 m (ISO Auto)	Image Play	Editing	Trimming, Re-sizing, Rotating, Effect
	Recharging time	Approx. 6 sec.			Digital output connector: USB 2.0
Sharpness		Soft, Normal, Vivid	Interface		Audio: Mono, Video output: NTSC or PAL (user
Effect		Normal, B&W, Sepia, Negative, Red, Green, Blue,			selectable), Pictbridge, DC power via cradle (opt.)
		Negative, RGB	Power Source  Dimensions (w x h x d)		2x AA alkaline, 2x AA Ni-MH (recommended)
Date Imprinting		Date, Date & Time, Date Off (user selectable)			Charger (optional): Inca PC-81 Rapid Charger
White Balance		Auto, Daylight, Cloudy, Fluorescent_H,			99.6 x 61.8 x 26.95 mm (excluding projecting parts)
		Fluorescent_L, Tungsten, Custom	Weight		Approx. 136 gm (without batteries or card)
Voice Recording		Voice recording (Max. 1 Hr)	Operating Temperature		0 ~ 40°C
		Voice Memo in Still Image (max. 10 sec.)	Operating Humidity		5 ~ 85%
Shooting	Still Image	Modes: Auto, Program, Manual, Movie, Scene*,	Software	Camera Driver	Storage driver (Windows 98/98SE/2000/ME/XP,
		*Scene: Night, Portrait, Children, Landscape, Sunset,			Mac OS 9.2 ~ 10.3)
		Dawn, Backlight, Fireworks, Close-up, Beach / Snow,		Application	Digimax Master includes still image editing and mov
		Continuous shooting, Self-timer: 2 sec, 10 sec			clip editing.
		MJPEG-4 Size: 640x480, 320x240, 160x128			User friendly "Effect" button, easy grip, large LCD,
	Movie Clip	Frame rate: 30 fps, 15 fps. With or without audio,	Special Featur	res	convenient dial mode. Self-timer: 2 sec., 10 sec.,
		Continuous, pause & resume, single image capture.			Double (10 sec., 2 sec.)

<sup>\*</sup> Specifications are subject to change without prior notice. All trademarks are the property of their respective owners

